





ASCO™ MINIATURE SOLENOID VALVES

PTFE DIAPHRAGM FLUID ISOLATION VALVES

- PTFE isolation valves are designed for use with highly aggressive liquids
- The PTFE body and diaphragm isolates the internal solenoid components from the media
- Excellent self-draining capability and easy-to-flush low-volume internal cavity
- Compact architecture make them ideal for analytical bench-top instrumentation
- Available in 2-Way normally closed, 2-Way normally open, and 3-Way universal; comes with #10-32, 1/4-28, or 1/8 NPSC in-line porting for exceptional versatility
- Meets all relevant CE directives
- Typical applications include:
 - Chromatography
 - Solvent Selection/Diversion
 - Sample Preparation
 - DNA Sequencing



Fluids*	Temperature Range	Seal Materials*
Aggressive liquids	0°C to 70°C (32°F to 158°F)	PTFE

*Ensure that the compatibility of the materials in contact with the fluids is verified

General Valve Information*	
Body	PTFE / Stainless steel
Poppet	PTFE
Diaphragm	PTFE
Response Time	< 20ms
Internal Volume	As low as 18 µl


* Ensure that the compatibility of the materials in contact with the fluids is verified

Electrical Characteristics	
Coil Insulation Class	F
Connector	22 AWG or 24 AWG Lead wires, 457mm (18in) long, PTFE coated
Standard Voltages	12 VDC, 24 VDC
Power Consumption	1.0 to 7.2 Watts

Specifications						
Connection	Orifice Size mm (inches)	Flow Coefficient		Operating Pressure bar (psi)		Power Rating (W)
		Kv (m³/h)	Cv	min.	max. gas / liquids	
#10-32	1.02 (0.040)	0.010	0.012	-0.9 (-13)	2.07 (30)	1
1/4-28	1.57 (0.062)	0.023	0.027	-0.9 (-13)	2.07 (30)	1.5
1/4-28	2.36 (0.093)	0.050	0.058	-0.9 (-13)	2.07 (30)	4.2
1/8 NPSC	3.96 (0.156)	0.186	0.215	-0.9 (-13)	2.07 (30)	7.2

01066GB-2019-R01

How to Order




ASCO™ MINIATURE SOLENOID VALVES

PTFE DIAPHRAGM FLUID ISOLATION VALVES

SERIES
055

Dimensions: mm (inches)



Configuration	Type	Catalog Number	Ø	A	B	C	D	E	F
2-Way NC	01	0055A101L0T00xx	19.05 (0.750)	29.34 (1.155)	12.70 (0.500)	9.220 (0.363)	12.70 (0.500)	-	#2-56
	02	0055A102L0T00xx	25.40 (1.000)	37.78 (1.488)	12.34 (0.486)	11.43 (0.450)	17.45 (0.687)	-	#4-40
	04	0055A103L0T00xx	31.75 (1.250)	47.32 (1.863)	15.90 (0.626)	12.70 (0.500)	22.45 (0.884)	38.10 (1.500)	
	04	0055A104L0T00xx	38.10 (1.500)	53.04 (2.088)	20.22 (0.796)	14.27 (0.562)	28.58 (1.125)	44.45 (1.750)	
2-Way NO	01	0055A201L0T00xx	19.05 (0.750)	29.54 (1.163)	12.70 (0.500)	9.220 (0.363)	12.70 (0.500)	-	#2-56
	03	0055A202L0T00xx	25.40 (1.000)	37.91 (1.493)	17.45 (0.687)	11.43 (0.450)	17.45 (0.687)	-	#4-40
	05	0055A203L0T00xx	31.75 (1.250)	46.06 (1.814)	22.45 (0.884)	12.70 (0.500)	22.45 (0.884)	38.10 (1.500)	
	05	0055A204L0T00xx	38.10 (1.500)	51.78 (2.039)	28.58 (1.125)	14.27 (0.562)	28.58 (1.125)	44.45 (1.750)	
3-Way	01	0055A301L0T00xx	19.05 (0.750)	29.49 (1.161)	12.70 (0.500)	9.220 (0.363)	12.70 (0.500)	-	#2-56
	03	0055A302L0T00xx	25.40 (1.000)	37.88 (1.492)	17.45 (0.687)	11.42 (0.450)	17.45 (0.687)	-	#4-40
	05	0055A303L0T00xx	31.75 (1.250)	46.06 (1.814)	22.45 (0.884)	12.70 (0.500)	22.45 (0.884)	38.10 (1.500)	
	05	0055A304L0T00xx	38.10 (1.500)	51.75 (2.038)	28.58 (1.125)	14.27 (0.562)	28.58 (1.125)	44.45 (1.750)	

01066GB-2019-R01

