


SPECIAL FLUIDS HOT WATER AND STEAM

Product Index



Function	ΔP		Temperature		Pipe connections	Series	Page
	min. (bar)	max. (bar)	min. (°C)	max. (°C)			
SOLENOID VALVES, BRASS BODY							
2/2 NC	0	6	-20	+160/165	 1/4 - 3/8	263	V901-09
2/2 NC	0/0,3	10	-20	+177	3/8 .. 1	220	V901-11
2/2 NC	0	9	-20	+150	3/8 .. 3/4	222	V901-15
2/2 NC	0,35	10	-20	+184	1 1/4 .. 2	220	V901-25
PRESSURE OPERATED VALVES, BRONZE BODY							
2/2 NC-NO	0	16	-10	+184	3/8 .. 2 1/2	E290	V901-46-1
2/2 NC-NO	0	16	-10	+184	Flanged DN 25 .. 50	T290	V901-46-1
2/2 NC-NO	0	16	-10	+184	1/2 .. 2	165 (AD/TBT)	V901-46-3
2/2 NC	0	16	-10	+184	Flanged DN 15 .. 80	165 (AD/BBT)	V901-46-3
3/2 NC-NO	0	16	-10	+184	1/2 .. 2	E390	V901-46-1
3/2 NO	0	16	-10	+184	1/2 .. 2	166 (AD/TBT)	V901-46-3
PRESSURE OPERATED VALVES, STAINLESS STEEL BODY							
2/2 NC-NO	0	16	-10	+184	3/8 .. 2 1/2	E290	V901-46-1
2/2 NC-NO	0	16	-10	+184	External thread 1/2 .. 1	U290	V901-46-1
2/2 NC-NO	0	16	-10	+184	External thread, food connections DIN 11851 Rd 28x8 .. 44x6	Y290	V901-46-1
2/2 NC-NO	0	16	-10	+184	Clamp / butt welding DN 10 .. 65	S290	V901-46-1
2/2 NC-NO	0	40	-25	+250	1/2 .. 2	E298	V901-46-2
2/2 NC-NO	0	40	-25	+250	Flanged (DIN and ANSI Class 300) DN 15..50	T298	V901-46-2
2/2 NC-NO	0	40	-25	+250	Socket welding ends DN 15..50	S298	V901-46-2
3/2 U	0	40	-25	+250	1/2 .. 2	E398	V901-46-2
3/2 U	0	40	-25	+250	Flanged (DIN and ANSI Class 300) DN 15..50	T398	V901-46-2
3/2 U	0	40	-25	+250	Socket welding ends DN 15..50	S398	V901-46-2
2/2 NC-NO	0	24	-10	+240	External thread M25x1,5..M36x2	R298	V901-54
2/2 NC-NO	0	24	-10	+240	Pad mounting DN 10 .. 32	R298	V901-56

00098GB-2016/R02
Availability, design and specifications are subject to change without notice. All rights reserved.

All leaflets are available on: www.asco.com



青岛秉诚自动化设备有限公司
地址：中国·青岛市重庆南路99号海尔云街甲3号楼7F

服务热线：4006-918-365
网址：<http://www.asco.store>

传真：(86-532)585-10-365
Email：sales@bechinas.com

V901-01-1

H

pipe connections		body material		max. operating pressure differential (bar)		fluid temperature range		power coil		series		page			
<ul style="list-style-type: none"> - internal thread - external thread - butt welding - ext. thread DIN 11851 - socket welding ends 		<ul style="list-style-type: none"> - flanged - clamp - pad mounting 				AC (~) DC (=)		min. max. AC DC max.		AC (~) DC (=)					
1/4 3/8 (M25x1.5) 1/2 3/4 (M30x2) 1 1 1/4 1 1/2 2 2 1/2 3		bronze brass cast iron stainless steel st. steel, AISI 316L		orifice size (mm) DN min. operating pressure differential (bar)		hot water steam hot water steam hot water steam superheated water		max. allowable pressure (bar)		(°C)		(W)		series page	
2/2 SOLENOID VALVES - NORMALLY CLOSED (NC)															
[Symbol]		[Symbol]		4		14,5		7,6		-20		+165		10,1	
[Symbol]		[Symbol]		5,6		6,6		4,8		-20		+160		10,1	
[Symbol]		[Symbol]		4		13,8		7,6		-20		+165		10,1	
[Symbol]		[Symbol]		5,6		6,6		4,8		-20		+160		10,1	
[Symbol]		[Symbol]		12,7		10		3		6,9		3,4		-20 +147 +177 - 10,1 15,6	
[Symbol]		[Symbol]		19		0,3		10		9		-		-20 +177 - 10,1 -	
[Symbol]		[Symbol]		25		0,3		10		3		-		-20 +147 - 10,1 -	
[Symbol]		[Symbol]		16		0		3,5		-3,5		-		-20 +150 +150 - 10,5 16,8	
[Symbol]		[Symbol]		19		0		3,5		-3,5		-		-20 +150 +150 - 10,5 16,8	
[Symbol]		[Symbol]		25		0		9		2		-		-20 +130 +130 - 15,4 -	
[Symbol]		[Symbol]		32		0		9		2		-		-20 +130 +130 - 15,4 -	
[Symbol]		[Symbol]		28		0,35		10		3,5		-3,5		-20 +150 +150 - 10,5 16,8	
[Symbol]		[Symbol]		44		0,35		10		3,5		-3,5		-20 +150 +150 - 10,5 16,8	
[Symbol]		[Symbol]		28		0,35		10		3,5		-3,5		-20 +184 - 10,5 -	
[Symbol]		[Symbol]		44		0,35		10		3,5		-3,5		-20 +184 - 10,5 -	
2/2 PRESSURE OPERATED VALVES - NORMALLY CLOSED (NC) AND NORMALLY OPEN (NO)															
[Symbol]		[Symbol]		10		0		-		16		10		-16 -10 - +184 - -	
[Symbol]		[Symbol]		65		0		-		16		10		-16 -10 - +184 - -	
[Symbol]		[Symbol]		15		0		-		24		24		24 40 -25 - +223 - -	
[Symbol]		[Symbol]		50		0		-		24		24		24 40 -25 - +223 - -	
[Symbol]		[Symbol]		15		0		-		16		10		-16 -10 - +184 - -	
[Symbol]		[Symbol]		50		0		-		16		10		-16 -10 - +184 - -	
[Symbol]		[Symbol]		15		0		-		24		24		24 40 -10 - +223 - -	
[Symbol]		[Symbol]		20		0		-		24		24		24 40 -10 - +223 - -	
[Symbol]		[Symbol]		10		0		-		24		24		24 40 -10 - +223 - -	
[Symbol]		[Symbol]		20		0		-		24		24		24 40 -10 - +223 - -	
[Symbol]		[Symbol]		32		0		-		24		24		24 40 -10 - +223 - -	
3/2 PRESSURE OPERATED VALVES - NORMALLY CLOSED (NC) AND NORMALLY OPEN (NO)															
[Symbol]		[Symbol]		15		0		-		16		10		-16 -10 - +184 - -	
[Symbol]		[Symbol]		50		0		-		16		10		-16 -10 - +184 - -	
3/2 PRESSURE OPERATED VALVES - UNIVERSAL (U)															
[Symbol]		[Symbol]		15		0		-		24		24		24 40 -25 - +223 - -	
[Symbol]		[Symbol]		50		0		-		24		24		24 40 -25 - +223 - -	
3/2 PRESSURE OPERATED VALVES - NORMALLY OPEN (NO)															
[Symbol]		[Symbol]		15		0		-		16		10		-16 -10 - +184 - -	
[Symbol]		[Symbol]		50		0		-		16		10		-16 -10 - +184 - -	

00098GE-2016/R01
Availability, design and specifications are subject to change without notice. All rights reserved.