

# 4/2, 5/2 AND 5/3 SOLENOID VALVES DIRECT OR PILOT OPERATED

Product Index



Function	$\Delta P$		Temperature		Pipe connections	Series	Page
	min. (bar)	max. (bar)	min. (°C)	max. (°C)			
<b>BRASS BODY</b>							
4/2	0	9	-20	+70	monostable/bistable	1/4 - 3/8	V803
4/2	0,7	17	-20	+85	monostable	1/4 .. 1	V805
5/2	0	10	-40	+60	monostable/bistable, IP67, IEC 61508	1/4	V826
5/2 (3/2 NC)	0	10	-40	+60	NAMUR, monostable/bistable, IP67, IEC 61508	1/4	V872
<b>ALUMINIUM BODY</b>							
5/2-5/3	2	10	-25	+60	monostable/bistable, IEC 61508	1/4 - 1/2	V820
5/2-5/3	0	10	-25	+60	monostable/bistable, IP67, IEC 61508	1/4 - 1/2	V821
5/2 (3/2 NC) - 5/3	2	10	-25	+60	NAMUR, monostable/bistable, IEC 61508	1/4 - 1/2	V860
5/2 (3/2 NC) - 5/3	0	10	-25	+60	NAMUR, monostable/bistable, IP67, IEC 61508	1/4 - 1/2	V862
5/2 (3/2 NC)	2	8	-20	+60	NAMUR, monostable/bistable, IP65	1/4	V865
<b>ACCESSORIES AND OPTIONS</b>							
Supply rail for series 551/553... (5/2-5/3)						-	V614 Sect.E

G

00090GB-2016/R01  
Availability, design and specifications are subject to change without notice. All rights reserved.

(Potentially explosive atmospheres, see page 3)

All leaflets are available on: [www.asconumatics.eu](http://www.asconumatics.eu)



青岛秉诚自动化设备有限公司  
地址：中国·青岛市重庆南路99号海尔云街甲3号楼7F

服务热线：4006-918-365  
网址：<http://www.asco.store>

传真：(86-532)585-10-365  
Email：[sales@bechinas.com](mailto:sales@bechinas.com)

V800-1





